

# LED 3528/5050 Flexible Light Strip



型号	光色	输入电压	电流	尺寸	每米灯数量	波长	流明	功率	光束角	包装
Item No.	Colors	Voltage	Current	Size (mm)	LED QTY/m	Wavelength	Lumen	Power/m	Angle	Package
PM-3528-60R	Red	DC-12V	0.4A	1000×8×0.22	60	620-630 nm	90	≤4.8W	120°	5m/reel
PM-3528-60G	Green	DC-12V	0.4A	1000×8×0.22	60	520-525 nm	240	≤4.8W	120°	5m/reel
PM-3528-60B	Blue	DC-12V	0.4A	1000×8×0.22	60	465-470 nm	60	≤4.8W	120°	5m/reel
PM-3528-60Y	Yellow	DC-12V	0.4A	1000×8×0.22	60	590-595 nm	90	≤4.8W	120°	5m/reel
PM-3528-60W	White	DC-12V	0.4A	1000×8×0.22	60	CCT 5500-6500K	300	≤4.8W	120°	5m/reel
PM-3528-60WW	Warm White	DC-12V	0.4A	1000×8×0.22	60	CCT 3000-3500K	240	≤4.8W	120°	5m/reel

型号	光色	输入电压	电流	尺寸	每米灯数量	波长	流明	功率	光束角	包装
Item No.	Colors	Voltage	Current	Size (mm)	LED QTY/m	Wave-length	Lumen	Power/m	Angle	Package
PM-5050-60R	Red	DC-24V	0.6A	1000×10×0.22	60	620-630 nm	270	≤14.4 W	120°	5m/reel
PM-5050-60G	Green	DC-24V	0.6A	1000×10×0.22	60	520-525 nm	720	≤14.4 W	120°	5m/reel
PM-5050-60B	Blue	DC-24V	0.6A	1000×10×0.22	60	465-470 nm	180	≤14.4 W	120°	5m/reel
PM-5050-60Y	Yellow	DC-24V	0.6A	1000×10×0.22	60	590-595 nm	270	≤14.4 W	120°	5m/reel
PM-5050-60W	White	DC-24V	0.6A	1000×10×0.22	60	CCT 5500-6500K	960	≤14.4 W	120°	5m/reel
PM-5050-60WW	Warm White	DC-24V	0.6A	1000×10×0.22	60	CCT 3000-3500K	960	≤14.4 W	120°	5m/reel

Note: Full color RGB light strips are also available, include remote light control functions like: flash; strobe; fade and smooth. Please visit our website for more information.